



Kinco + ¸ © Ĩ Ô µ

10• •% £
¾ y Ñ² i ÷ ^
 < µ ò † + ¸ Ñ Ĩ ĩ Ũ kw¨ 4 Â E g y Ñ ÷ ^ ´ k ... é [² i ÷ ^ + € 0• £ z
20• Å Ý
¾ ä ê Å 0• ä € •
 J + N Ü •" k + N Ñ F i À X @ p•r k [\ V U•U p ^ x• 7 Ñ p•î P p•P 7 P b i í³ — T — Â ñ f P Ð¾ @ N I V ù Ð

Kinco FD2S x æ û Ž u § « — ê ± ? d

FD2S© ç + ċ v Æ Ü ~ Đ @ f n

¹ Y ? d		FD412S-AA-000	FD422S-AA-000	FD432S-AA-000
>	>	% , AC220V -20/+15% 47 ½63Hz		% , ê , AC220V -20/+15% 47 ½63Hz
	.p >	18VDC ½30VDC 1A		
v	Â Ý Ò ÿ ß vgrms h	3A	4A	11A
	Q > v (peak)	10A	15A	27.5A
F Ø ' Z		u 4 ä ä 0.1um C Y ° ð > y M ð >		

Kinco DD2S x æ û Ž u š « — ê ± ? d

DD2S© ç + ċ v Æ Ü ~ Đ @ f n

¹ Y ? d		DD412S -AA -000	DD422S -AA -000	DD432S -AA -000
>	>	%, AC220V -20/+15% 47 ½63Hz		%, ê , AC220V -20/+15% 47 ½63Hz
	.p >	18VDC ½30VDC 1A		
v	Ã Ý Ò ÿ ß v(rms)	3A	4A	11A
	Q > v (PEAK)	10A	15A	27.5A
F Ø ' Z		u 4 ä ä 0.1um C Y ° ð > y M ð >		
ô ò		¬ } Û N ò Š g Ÿ G g Œ Ñ ò k } • " Ä, Ü « ` h		
ô ò 9*} v µ		DC380V±5V		
9 Š 9		DC400V±5V		
>¬ 9 Š 9		DC200V±5V		
Ò 0 • "		À Ò 0		ò î Ò
MO		1.2kg		2.4kg
y	Ã Ý Ÿ µ Ĩ È ä	[n Ÿ • " y4MPPS k • ▯ â n Ÿ • " y200KPPS		
å	Ĭ 6 X % "	Ĭ + • g kCCW+CW kA ,+B , g 5V-24V h		
O	6 X u • • "	z * ĭ f g Ä B @ f — h		
ò	ù Ø Í	Ä B @ f —		
%				
"				

Kinco DD2S x æ û Ž u § « — ê ± ? d

DD2S© ç + ċ v Æ Ü ~ Đ @ f n

¹ Y ? d		DD412S -AA -000	DD422S -AA -000	DD432S -AA -000
f	ÿ µ •	7 è f ÿ µ k * COM1 € N c k U Y ä u g 12.5 ½ 30V h Ä k - U Y z u Ä		
		ÿ G ¬ } # k ò y		
ÿ ÿ µ		Ü ~ ... o • Ü ~ j " Ö y o • Ü ~ W • % " O ò o • , † ê A † O ò o • 3 ' y o • ċ ' y o • = µ ' Z o • 6 X F g o •		
µ				

Kinco SLM1 x æ ¥ - þ t Â û Ž Ô ² ê ± ? d

SLM1© ç Ä ^ / + ¿ Ñ Ð @ f n

4ì × ? d	\$ x	Ô ² ¹ Y			
		SLM1-W060 -	SLM1-W080 -	SLM1-W100 -	SLM1-W120 -
Q > P	N	260	394	513	648
4 Ò P	N	73	107	133	162
Ñ o f	N/(W ^{1/2})	12.2	15.4	17.9	20.2
Â Ý 4 Ò ô • ä	W	35.5	48.1	55.7	64.4
Q > v	Arms	10.0	10.0	10.0	10.0
4 Ò v	Arms	2.8	2.7	2.6	2.5
P o f	N/Arms	26.0	39.4	51.3	64.8
F g	Vp/(m/s)	21.2	32.2	41.9	52.9
, Š	ohms	2.2	3.2	4.0	5.0
, ß	mH	11.0	16.0	20.0	25.0
H Ž • o f	ms	5.0	5.0	5.0	5.0
Â Ý € 9	Vdc	540	540	540	540
Â Ý É Á “ †	-	120	120	120	120
¿ ¥ M O	kg	0.8	1.2	1.6	2.0
M ó U # x †	mm	96/144/192/240/288			
M*} –	kN	0.5	0.7	1.0	1.3
M â â Y	mm	24	24	24	24
M ó M O	kg/m	3.0	4.3	5.5	6.7

> *	% y	Ñ ° Z			
		SLM1-W060 -	SLM1-W080 -	SLM1-W100 -	SLM1-W120 -
CW	mm	60	80	100	120
MW	mm	55	75	95	115
DW	mm	36	56	76	96
H	mm	40			
A	mm	26 g Å • h	15 g — • h	32 g Å • h	28 g — • h
B	mm	/	45	64	84
C	mm	46	66	86	106
D	mm	14.5	15	15.5	15.5
N		6	8	10	8
X		4	4	4	5
Y	mm	6	6	6	10

Kinco SLM2 x æ ¥ - þ t Â û Ž Ô ² ê ± ? d

SLM2© ç Ä ^ / + ¿ Ñ Ð @ f n

4ì x ? d	\$ x	Ô ² ¹ Y			
		SLM2-W060 -	SLM2-W080 -	SLM2-W100 -	SLM2-W120 -
Q > P	N	515	809	1104	1300
4 Ò P	N	145	213	267	325
Ñ o f	N/(W ^{1/2})	17.2	22.1	25.6	29.5
Â Ý 4 Ò ô • ä	W	71.1	93.1	108.6	121.0
Q > v	Arms	10.0	10.0	10.0	10.0
4 Ò v	Arms	2.8	2.7	2.6	5.0
P o f	N/Arms	51.8	78.9	102.7	65.0
F g	Vp/(m/s)	42.3	64.4	83.9	53.1
, Š	ohms	4.4	6.2	7.8	2.4
, ß	mH	22.0	32.0	42.0	13.0
H Ž • o f	ms	5.0	5.2	5.4	5.5
Â Ý € 9	Vdc	540	540	540	540
Â Ý É Á “ †	-	120	120	120	120
¿ ¥ M O	kg	1.6	2.4	3.2	4.0
M ó U # x †	mm	96/144/192/240/288			
M*} –	kN	0.9	1.5	1.9	2.4
M â â Y	mm	24	24	24	24
M ó M O	kg/m	3.0	4.3	5.5	6.8

=)	\$ x	Ô ² ¹ Y			
		SLM2-W060 -	SLM2-W080 -	SLM2-W100 -	SLM2-W120 -
CW	mm	60	80	100	120
MW	mm	55	75	95	115
DW	mm	36	56	76 \$ • h	96 \$ • h
H	mm	40			

96 \$ • h

Kinco SLM3 x æ ¥ - þ t Â û Ž Ô º ê ± ? d

SLM3© ç Ä ^ / + ¿ Ñ Ð @ f n

Å @ f	% y	Ñ ° Z			
		SLM3-W060 -	SLM3-W080 -	SLM3-W100 -	SLM3-W120 -
Q > P	N	718	1128	1539	1948
4 Ò P	N	201	305	400	487
Ñ o f	N/(W ^{1/2})	19.8	25.9	31.5	36.3
Â Ý 4 Ò ô • ä	W	103.4	138.2	161.5	180.3
Q > v	Arms	10.0	10.0	20.0	20.0
4 Ò v	Arms	2.8	2.7	5.2	5.0
P o f	N/Arms	71.8	112.8	76.9	97.4
F g	Vp/(m/s)	58.6	92.1	62.8	79.5
, Š	ohms	6.4	9.2	2.9	3.5
, ß	mH	33.0	48.0	15.0	18.0
H Ž • o f	ms	5.2	5.2	5.2	5.1
Â Ý € 9	Vdc	540	540	540	540
Â Ý É Á " †	-	120	120	120	120
¿ ¥ M O	kg	2.3	3.6	4.8	6.0
M ó U # x †	mm				

=)	\$ x	Ô ² ¹ Y			
		SLM3-W060 -	SLM3-W080 -	SLM3-W100 -	SLM3-W120 -
CW	mm	60	80	100	120
MW	mm	55	75	95	115
DW	mm	36	56	76	96
H	mm	40			
A	mm	26 g Å • h	15 g — • h	32 g Å • h	28 g — • h
B	mm	/	45	64	84
C	mm	46	66	86	106
D	mm	14.5	15	15.5	15.5
N		6	8	10	8
X		4	4	4	5
Y	mm	6	6	6	10

Kinco SLI 2 x æ x - þ U ¹ û Ž Ô ² ê ± ? d

SLI2© ç — ^ / + ¿ Ñ Ð @ f n

4ì × ? d	\$ x	Ô ² ¹ Y			
		SLI2-L61-	SLI2-L91-	SLI2-L121-	SLI2-L181-
Q > P	N	88	132	176	264
Ö P	N	18	26	35	53
S (1/2)		4.3	5.3		

Kinco SLI3 x æ x - þ U ¹ û Ž Ô ² ê ± ? d

SLI3© ç — ^ / + ¿ Ñ Ð @ f n

4ì × ? d	\$ x	Ô ² ¹ Y		
		SLI3-L121-	SLI3-L181-	SLI3-L241-
Q > P	N	289	432.3	579
4 Ò P	N	58	86	116
Ñ o f	N/(W ^{1/2})	11.2	13.8	15.8
Â Ý 4 Ò ô • ä	W	27.0	39.1	54.0
Q > v	Arms	8.4	8.4	8.4
4 Ò v	Arms	1.7	1.7	1.7
P o f	N/Arms	34.5	51.8	69.0
F g	Vp/(m/s)	28.2	42.3	56.4
, Š	ohms	9.4	14.1	18.8
, ß	mH	6.3	9.4	12.5
H Ž • o f	ms	0.67	0.67	0.67
Â Ý € 9	Vdc	330	330	330
Â Ý É Á “ †	-	120	120	120
M ó U # x †	mm	240/300/360/420/480/540/600		
¿ ¥ M O	kg	0.405	0.608	0.81
¿ ¥ x †	mm	121	181	241
M*} –	N	0	0	0
M â å Y	mm	60	60	60
M ó M O	kg/m	8.78	8.78	8.78

SLI4© ç — ^ / + ¿ Ñ Ð @ f n

4ì × ? d	\$ x	Ô ²¹ Y				
		SLI4-L121-	SLI4-L181-	SLI4-L241-	SLI4-L301-	SLI4-L361-
Q › P	N	336	505	673	842	1010
4 Ò P	N	68	102	136	170	204
Ñ o f	N/(W ¹/²)	12.5	15.3	17.7	19.8	21.6
Ò ô • ä	W	29.7	44.6	59.5	74.4	89.2



Kinco SLI 6 x æ x - þ U ¹ û Ž Ô ² ê ± ? d

SLI6© ç — ^ / + ċ Ñ Đ @ f n

4ì × ? d

\$ x

PROVEN P